
# Saturn 8000 2530FW

Premium Flat Panel Detector for General Radiography






High Image Quality: 99  $\mu$ m



25 cm x 30 cm



Finest Durability




**Greater Mobility** 

### SATURN 8000

#### **Features**

- Glass-free TFT. Active area of 25 cm x 30 cm.
- High spatial resolution with 99 μm pixel array.
- IP67 dust and water resistance.
- Multiple charging with various methods standard USB–C interface, magnetic tether connector, cradle, battery charger.
- Long lasting battery up to 8 hours of operation.
- NFC card for different x-ray room settings.
- Various applications such as General Radiography, Veterinary, Podiatric, Equine X-ray systems.
- Advanced algorithm for image enhancement by Photonunderstanding Al Solution.

## **Drawing**



## **Technical Specifications**

Model Name	FXRD-2530FAW
Technology	a–Si Flexible TFT
Scintillator	CsI
Pixel Pitch	99 µm
Spatial Resolution	5.0 lp/mm
Pixel Matrix	2524 x 3036 pixels
Image Size	25 cm x 30 cm
Grayscale	16 bits
Image Acquisition Time	3 s
Recommended Cycle Time	5 s
Data Interface	Gigabit Ethernet IEEE 802.11n / ac
X-ray Generator Interface	DR Trigger Mode / AED Mode / Software Trigger
Dimensions	28.3 cm x 33.3 cm x 1.5 cm
Weight	1.7 kg (1 battery)
Battery	Lithium Ion 3400mAh x 1 8 h (standby) * 1,500 images at a 15-second cycle.
Dust and Water Resistant	IP67
X–ray Voltage Range	40 – 150 kVp
Operating Environment	0°C to 40°C 5 % to 90 % RH (non-condensing)
Power	Normal: Max. 24W Charging: Max. 50W

 $\ensuremath{\star}$  Specifications are subject to change without prior notice.



41–3, Burim–ro 170 beon–gil, Dongan–gu, Anyang–si, Gyeonggi–do, 14055 Republic of Korea Tel +82–70–7011–6161 Web www.vieworks.com

#### Sales Office

New Medical Imaging Co., Ltd. 7th floor, No.31, Sec.2 Zhongyang S. Rd., Beitou Dist., Taipei City 112, Taiwan Tel: +886-2-2892-2275 Email: sales@newmedical.com.tw

