

Features

- \$FWLYH DUHD RI ϕ [ϕ
- +LJK VSDWLDO UHVROXWLRQ ZLWK SL[HO DUUD\
- ,3 GXVW DQG ZDWHU UHVLVWDQFH
- &RQYHQLHQW FKDUJLQJ ZLWK YDULRXV PHWKRGV VWDQGDUG 86% LQWHUIDFH PDJQHWLF WHWKHU FRQQHFWRU FUDGOH
- /RQJ ODVWLQJ EDWWHU\ XS WR KRUV RI RSHUDWLRQ
- 9LHZHU VRIWZDUH UXQQQLQJ RQ :LQGRZV% 26 9;YXH%
- 9DULRXV DSSOLFDWLRQV VXFK DV *HQHUDO 5DGLRJUDSK\ 9HWHUL DUUD\ ORELOH ; UD\ V\ VWHPV

Drawing



Technical Specifications

Model Name) ; 5'	9\$:) ; 5'	9\$: 3/86
7HFKQRORJ\			a-Si TFT with photodiode	
6FLQWLLOODWRU			Csl	
3L[HO 3LWFK				
6SDWLDO 5HVROXWLRQ			OS i	
3L[HO 0DWUL[[SL[HOV	
Image Size			ϕ [ϕ	
*UD\VFDOH			ELWV	
,PDJH \$FTXLVLWLRQ 7LPH			3s	
5HFRPPHQGHG &\FOH 7LPH			V	
'DWD ,QWHUIDFH			*LJDELW (WKHUQHW ,(((Q DF	
; UD\ *HQHUDWRU ,QWHUIDFH			'5 7ULJJHU ORGH \$(' ORGH	
'LPHQVLRQV			ϕ [ϕ [ϕ	
Weight		2.95 kg		3.1 kg
		3.15 kg		3.3 kg
Battery			/LWKLXP ,RQJ K VWDQGEy) LPDJHV DW D VHFRRG F\FOH	
Dust and Water Resistant			,3	
X-ray Voltage Range			N9S	
Operating Environment			WR WR 5+ QRQ FRQGHQVLQJ	
Power			1RUPDO 0D[: &KDUJLQJ 0D[:	

6SHFLILFDWLRQV DUH VXEMHFW WR FKDQJH